

1 . Product Type: Unique identification code of the product-type:

## Monocal Blanc Polaire - VPI

2. Type batch or serial number

See packaging : product type, batch number, date of manufacturing, place of manufacturing

3. Intended use or uses

factory-made rendering mortar (OC) based on inorganic binders for external use on walls, ceilings, columns and partitions.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer

Société VPI SAS  
4, rue Aristide Bergès B.P. 34  
F - 38081 L'ISLE D'ABEAU Cedex  
[www.vpi.vicat.fr](http://www.vpi.vicat.fr)

5. Contact Address: name and contact address of the authorized representative

Not relevant

6. AVCP: System or systems of assessment and verification of constancy of performance

System 4

7. Approved body (hEN):

In case of the declaration of performance(DoP)concerning a construction product covered by a designated standard:

The manufacturer has determined the performances on tests, and according to the system 4 factory production control

8. Approved body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

Not relevant

9 Declared performance :

Caractéristiques essentielles	Performances	Spécifications techniques harmonisées
Reaction to fire	A1 Class	EN 998-1 : 2016
water absorption	Wc2	
water vapor permeability	$\mu = 11$	
Thermal conductivity	NPD ( Not Determined Performance)	
Durability (freeze /thau resistance)		
Adhesion after weathering cycles	$\geq 0,2 \text{ N/mm}^2$ – FP : B	
water permeability after weathering cycles	$\leq 1 \text{ ml/cm}^2$ at 48h	

10. Declaration: The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Patrick LAVEZZARI Directeur Général  
L'Isle d'Abeau Le 13/03/2019

