



MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.
Issue date: 2/25/2021 Revision date: 5/29/2024 Supersedes version of: 2/15/2024 Version: 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : MASONRY REPAIR FILLER
Product code : ENUK-BAT-TTTHR
Type of product : Powders
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Fillers, putties, plasters, modelling clay.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

TOUPRET SA
24 Rue du 14 juillet
FR 91813 Corbeil-Essonnes
France
T + 33 (0)1 69 47 20 20, F + 33 (0)1 60 75 87 11
fdstoupret@toupret.fr, <https://www.toupret.com/>

Subsidiary companies

TOUPRET UK LTD
Capital Business Centre - Unit 58
22 Carlton Road
UK CR2 0BS South Croydon
United Kingdom
T +44 208 916 2134, F +44 208 916 2136
fdstoupret@toupret.fr, <https://www.toupret.co.uk/>

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Edinburgh Centre) Royal Infirmary of Edinburgh	Little France Crescent EH16 4SA	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Causes serious eye damage. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05

GHS07

Signal word (CLP)

: Danger

Contains

: Cement, portland, chemicals; Flue dust, portland cement

Hazard statements (CLP)

: H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
: P261 - Avoid breathing dust.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor.
P312 - Call doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).

Precautionary statements (CLP)

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cement, portland, chemicals substance with national workplace exposure limit(s) (GB)	CAS-No.: 65997-15-1 EC-No.: 266-043-4	1.545 – 30.9	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Limestone substance with national workplace exposure limit(s) (GB)	CAS-No.: 1317-65-3 EC-No.: 215-279-6	≥ 25 – < 50	Not classified
Quartz (SiO ₂) substance with a Community workplace exposure limit	CAS-No.: 14808-60-7 EC-No.: 238-878-4	> 23.8	Not classified
Ashes (residues)	CAS-No.: 68131-74-8 EC-No.: 268-627-4	≤ 10.815	Eye Irrit. 2, H319
substance with national workplace exposure limit(s) (GB)	CAS-No.: 546-93-0 EC-No.: 208-915-9	≥ 1 – < 5	Not classified
Cellulose substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 9004-34-6 EC-No.: 232-674-9	≥ 1 – < 5	Not classified
Flue dust, portland cement	CAS-No.: 68475-76-3 EC-No.: 270-659-9 REACH-no: 01-2119486767- 17	≤ 1.545	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
Calcium dihydroxide substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 1305-62-0 EC-No.: 215-137-3 REACH-no: 01-2119475151- 45	0.15 – 0.3	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Calcium sulphate substance with national workplace exposure limit(s) (GB)	CAS-No.: 7778-18-9 EC-No.: 231-900-3 REACH-no: 01-2119444918- 26	> 0.15	Not classified

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Take off contaminated clothing. Gently wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a doctor immediately, even if there are no immediate symptoms.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Product dust may cause mechanical irritation to the skin and mucous membranes.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. May cause moderate irritation. Repeated or prolonged skin contact may cause irritation progressing to a burn.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Large amounts: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. nausea, vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clear up rapidly by scoop or vacuum. Do not use any water to clean up. Product forms slippery surface when combined with water.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Do not breathe dust. Avoid contact with skin and eyes. Keep out of reach of children.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Protect from moisture. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Cement, portland, chemicals (65997-15-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Portland cement
WEL TWA (OEL TWA)	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Calcium dihydroxide (1305-62-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Calcium hydroxide
WEL TWA (OEL TWA)	5 mg/m ³ 1 mg/m ³ Respirable fraction
WEL STEL (OEL STEL)	4 mg/m ³ Respirable fraction
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Cellulose (9004-34-6)	
United Kingdom - Occupational Exposure Limits	
Local name	Cellulose
WEL TWA (OEL TWA)	10 mg/m ³ inhalable dust 4 mg/m ³ respirable
WEL STEL (OEL STEL)	20 mg/m ³ inhalable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Calcium sulphate (7778-18-9)	
United Kingdom - Occupational Exposure Limits	
Local name	Plaster of Paris
WEL TWA (OEL TWA)	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Limestone (1317-65-3)	
United Kingdom - Occupational Exposure Limits	
Local name	Calcium carbonate (Limestone, Marble)
WEL TWA (OEL TWA)	10 mg/m ³ total inhalable 4 mg/m ³ respirable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
(546-93-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Magnesite
WEL TWA (OEL TWA)	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Safety glasses. Protective clothing. Gloves. Dust production: dust mask with filter type P2.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses with side shields. Do not wear contact lenses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In order to avoid inhalation of dust, all sanding must be done wearing adequate respirator. dust mask P2

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powders.
Colour	: Grey.
Odour	: characteristic.
Odour threshold	: No data available
pH	: 12 – 13
pH solution	: 35 % (20 °C)
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Flammability	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: ≈ 1.79
Solubility	: Dispersible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosive properties	: Not explosive.
Oxidising properties	: Non oxidizing.
Explosive limits	: Not applicable
Particle size	: Not available

9.2. Other information

VOC content : < 0.02 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Exothermic reaction with water.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Acids. Aluminium.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)

Cement, portland, chemicals (65997-15-1)	
LD50 oral	> 2000 mg/kg
LD50 dermal	> 2000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	> 5 mg/l/4h
Calcium sulphate (7778-18-9)	
LD50 oral rat	> 1581 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Calcium sulphate (7778-18-9)	
LC50 Inhalation - Rat	> 3.26 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
(546-93-0)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
Skin corrosion/irritation	: Causes skin irritation. pH: 12 – 13
Serious eye damage/irritation	: Causes serious eye damage. pH: 12 – 13
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Additional information	: Prolonged and repeated skin contact may cause a sensitising effect due to the presence of track of elements such as chromium VI
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)

Calcium sulphate (7778-18-9)	
NOAEL (chronic, oral, animal/male, 2 years)	256 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	284 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)

Calcium sulphate (7778-18-9)	
LOAEL (oral, rat, 90 days)	237 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	79 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Aspiration hazard	: Not classified (Technical impossibility to obtain the data) (Technical impossibility to obtain the data)

MASONRY REPAIR FILLER	
Viscosity, kinematic	Not applicable

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)

Calcium sulphate (7778-18-9)	
LC50 - Fish [1]	> 79 mg/l Test organisms (species): Oryzias latipes
EC50 72h - Algae [1]	> 79 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

(546-93-0)

EC50 72h - Algae [1]

> 18.5 mg/l Test organisms (species): *Desmodesmus subspicatus* (previous name: *Scenedesmus subspicatus*)

12.2. Persistence and degradability

MASONRY REPAIR FILLER

Persistence and degradability

Not established.

12.3. Bioaccumulative potential

MASONRY REPAIR FILLER

Bioaccumulative potential

No bioaccumulation expected.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

MASONRY REPAIR FILLER

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Component

Calcium dihydroxide (1305-62-0)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Other adverse effects

: May cause pH changes in aqueous ecological systems.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1 UN number

UN-No. (ADR)

: Not applicable

UN-No. (IMDG)

: Not applicable

UN-No. (IATA)

: Not applicable

UN-No. (ADN)

: Not applicable

UN-No. (RID)

: Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR)

: Not applicable

Proper Shipping Name (IMDG)

: Not applicable

Proper Shipping Name (IATA)

: Not applicable

Proper Shipping Name (ADN)

: Not applicable

Proper Shipping Name (RID)

: Not applicable

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)
VOC content : < 0.02 %
Other information, restriction and prohibition regulations : Directive 2004/42/EC on the limitation of emissions of volatile organic compounds. Regulation (EU) No 861/2010 related to Customs Nomenclature.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

This sheet was updated (refer to the date at the top of this page). This sheet has been revised completely (changes were not marked).

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
N.O.S.	Not Otherwise Specified
NOAEL	No-Observed Adverse Effect Level
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources : ECHA (European Chemicals Agency). Supplier's safety documents.

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

MASONRY REPAIR FILLER

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Full text of H- and EUH-statements:

H335	May cause respiratory irritation.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method

fds eu toupret

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.